

## Aluminium-Rohre

AW-6060 T66 EN 573-3, 755-1, 755-2, 755-9  
AlMgSi0,5 F22  
Stablängen = ca. 6 m

Vierkantrohre				Rechteckrohre	
mm	in kg/m	mm	in kg/m	mm	in kg/m
10x10x1	0,097	20x10x1,5	0,220	100x20x2	1,275
10x10x1,5	0,138	20x15x2	0,340	100x25x2	1,355
15x15x1,5	0,225	25x15x2	0,390	100x40x3	2,170
15x15x2	0,305	30x10x1,5	0,300	100x40x4	2,940
20x20x2	0,390	30x20x2	0,500	100x50x4	3,070
25x25x1,5	0,370	35x15x2	0,495	100x60x4	3,210
25x25x2	0,520	35x20x2	0,551	120x20x2	1,490
25x25x3	0,734	40x20x2	0,605	120x40x4	3,285
30x30x2	0,615	40x20x3	0,875	150x40x4	3,935
30x30x3	0,880	40x25x2	0,660	150x50x4	4,150
35x35x2	0,755	40x30x2	0,715		
40x40x2	0,845	40x30x4	1,360		
40x40x2,5	1,050	50x20x2	0,715		
40x40x3	1,200	50x25x2	0,765		
40x40x4	1,560	50x30x2	0,820		
45x45x2	0,930	50x30x3	1,200		
50x50x2	1,037	50x40x2	0,930		
50x50x3	1,540	60x20x2	0,825		
50x50x4	1,960	60x30x2	0,960		
50x50x5	2,460	60x30x3	1,630		
60x60x3	1,850	60x34x3	1,425		
60x60x4	2,420	60x40x2	1,068		
70x70x2	1,470	60x40x3	1,525		
80x80x2	1,690	60x40x4	1,990		
80x80x3	2,500	70x20x2	0,935		
80x80x4	3,285	80x18x2	1,015		
100x100x3	3,143	80x20x2	1,040		
100x100x4	4,150	80x40x4	2,420		
120x120x2,5	3,200	80x50x2	1,400		
120x120x5	6,210	80x50x4	2,640		