

Messing Rund- und Rändelstangen

Messing-Rundstangen

CW614N EN 12164 CuZn39Pb3 hart 1756 Stablängen = ca. 3 m					
Ømm	kg/m	Ømm	kg/m	Ømm	kg/m
1,5	0,015	16	1,710	50	16,690
1,8	0,021	17	1,929	55	20,190
2,0	0,027	18	2,163	60	24,030
2,5	0,042	19	2,410	65	28,210
2,8	0,052	20	2,670	70*	32,710
3,0	0,060	21	2,944	75*	37,550
3,5	0,082	22	3,231	80*	42,730
4,0	0,107	23	3,552	85*	48,230
4,5	0,135	24	3,844	90*	54,080
5,0	0,167	25	4,160	100*	66,760
5,5	0,202	26	4,512	110*	80,800
6,0	0,240	27	4,880	120*	96,100
6,5	0,282	28	5,232	130*	112,800
7,0	0,327	29	5,610	140*	130,800
7,5	0,376	30	6,008	150*	150,200
8,0	0,427	32	6,840	160*	171,000
8,5	0,482	33	7,270	180*	216,000
9,0	0,541	34	7,716	200*	267,000
10,0	0,668	35	8,180		
11,0	0,808	36	8,652		
12,0	0,961	38	9,640		
13,0	1,128	40	10,688		
14,0	1,308	42	11,780		
15,0	1,502	45	13,520		

* EN 12165 gepresst

Messing-Rändelstangen

CW614N CuZn39Pb3 Stablängen = ca. 2-3 m					
Ømm	kg/m	Ømm	kg/m	Ømm	kg/m
6,0	0,240	10,0	0,665	15,0	1,500
7,0	0,325	11,0	0,800	16,0	1,710
8,0	0,425	12,0	0,960		