

## Kupfer Rundstangen und Vierkantstangen

### Kupfer-Rundstangen

Cu-ETP (CW004A) EN 13601, 13605

E-Cu

Stablängen = ca. 4 m

Ømm	kg/m	Ømm	kg/m
3	0,063	35	8,560
4	0,112	40	11,200
5	0,175	45	14,150
6	0,252	50	17,500
8	0,447	60	25,200
10	0,699	70	34,250
11	0,850	80	44,800
12	1,010	90	56,700
14	1,370	100	70,000
15	1,570	110	85,000
16	1,790	120	101,000
18	2,270	130	118,100
20	2,800	140	137,000
22	3,390	150	157,000
25	4,370	160	179,000
28	5,500	180	226,400
30	6,290	200	279,500
32	7,200		

### Kupfer-Vierkantstangen

Cu-ETP (CW004A) EN 13601, 13605

E-Cu

Stablängen = ca. 4 m

Ømm	kg/m	Ømm	kg/m
6x6	0,321	40x40	14,250
8x8	0,570	45x45	18,050
10x10	0,890	50x50	22,250
12x12	1,290	60x60	32,050
15x15	2,000	70x70	43,610
18x18	2,880	80x80	57,000
20x20	3,560	100x100	89,000
25x25	5,560	120x120	128,000
30x30	8,010		
35x35	10,900		