

Kupfer Bleche und Rundrohre

Kupfer-Bleche					
EN 1172, 1652,13599 Tafelgröße: 1000 x 2000 mm Zuschnitte kurzfristig!					
Cu-DHP R220 Sf-Cu F20 Stärke in mm	Cu-DHP R240 Sf-Cu F25 Stärke in mm	Cu-ETP /Cu-OF R240 E-Cu/OF-Cu F25 Stärke in mm	ca.Gewicht je Tafel in kg		
-	0,3	-	5,300		
-	0,5	-	8,900		
-	0,6	-	10,680		
-	0,7	-	12,460		
-	0,8	-	14,200		
1,0	1,0	1,0	17,800		
-	1,2	-	21,800		
1,5	1,5*	1,5	26,800		
2,0	2,0	2,0	35,600		
-	2,5	-	44,600		
-	-	3,0	54,000		
-	-	4,0	71,200		
-	-	5,0	89,000		
-	-	6,0	108,000		
-	-	10,0	178,400		
-	-	20,0	357,000		
* auch im Format 1250 x 2500 mm					
Kupfer-Rohre					
Cu-DHP (CW024A) EN 12449,12451,1057,13600 Sf-Cu					
weich F20 in Ringen von 50m Stärke in mm	halbhart/hart F25-30 in Stangen von 5m Stärke in mm	Gewicht kg/m	weich F20 in Ringen von 50m Stärke in mm	halbhart/hart F25-30 in Stangen von 5m Stärke in mm	Gewicht kg/m
-	2x0,3	0,014	15x1,0	15x1,0	0,391
4x0,5	3x0,5	0,050	-	16x1,0	0,419
-	4x1,0	0,080	18x1,0	18x1,0	0,475
6x0,5	5x0,5	0,063	-	18x1,5	0,700
-	5x1,0	0,118	-	20x1,0	0,531
6x1,0	6x1,0	0,140	-	22x1,0	0,587
8x1,0	8x1,0	0,196	-	22x1,5	0,860
10x1,0	10x1,0	0,252	-	28x1,0	0,755
-	12x2,0	0,560	-	35x1,5	1,420
12x1,0	12x1,0	0,308	-	156x3,0	12,800
-	14x1,0	0,363			
-	14x2,0	0,670			
Aussendurchmesser x Wandstärke					