

Kupfer Vierkantrohre

(CW021A) EN 13600 SE-Cu (Cu-HCP)			
weich R200 Abmessung in mm	Längen in m	hart R290 Abmessung in mm	Längen in m
2x2x0,3*	4,80	2x2x0,3*	4,000
3x3x0,3*	5,80	4x4x0,5*	3,050
4x4x0,5*	4,52	5x5x0,5	5,50-6,00
5x5x0,5*	4,80	6x6x1,0	5,80-6,00
8x8x1,0	6,00-6,20	10x10x1,0	5,80-6,20
3x2x0,3*	4,30	12x12x1,0	6,00-6,20
5x3x0,5*	5,75	3x2x0,3	2,800
10x5x1,0*	6,00	5x3x0,5*	4,630
10x6x1,0	5,80-6,20	8x5x1,0*	6,300
15x10x1,0*	3,20	8x6x1,0	4,00-4,50
20x10x1,0	4,10-4,30	10x5x1,0*	5,400
28x6x1,0*	5,70	10x6x1,0*	5,400
		12x6x1,0*	6,000
		12x8x1,0	5,50-6,00
		15x10x1,0	5,50-6,00
		16x6x1,0	4,00-5,00
		20x10x1,0	6,200
		40x10x2*	5,050

* hierbei handelt es sich um Kommissionsware. Abverkauf und Verfügbarkeit bitte erfragen